



EnergyMiser™ Picture Window

Standard Features:

- Custom manufactured to your specifications or job requirements.
- Triple Pane -U-Factor .17 whole window insulation value.
- EnergyMiser™ triple pane glass saves energy and reduces street noise.
- Low profile frame for maximum glass area/visibility.
- DuraSeal Warm Edge Spacer.
- Fusion welded, multi-chambered 3 ¼" vinyl master frames.
- Fusion welded vinyl frame.

Options:

- Double Glass R4 (U-Factor .26) Insulation Value
- AccuBond™ Custom Color Match for Exterior
- Decorative Colonial or Georgian grids
- Tempered or Obscured glass

PERFORMANCE RATINGS

U-Factor (Insulation Value)	Double Glass = .26 (R3)	Triple Glass = .17 (R5)	SHGC: Double Glass = .34 Triple Glass = .27
Condensation Resistance	Double Glass = 62	Triple Glass = 73	
Visible Transmittance	Double Glass = .61	Triple Glass = .48	

ANSI/NFRC 100-2020: Procedure for Determining Fenestration Product U-Factors
 ANSI/NFRC 200-2020: Procedure for Determining Fenestration Product Solar Heat Gain Coefficient and Visible Transmittance at Normal Incidence
 NFRC 500-2017: Procedure for Determining Fenestration Product Condensation Resistance Values
 Program Versions Utilized: THERM/WINDOW 7.4;NFRC 101-2020[E1A9];NFRC Sim Manual 2020