

**EnergyMiser™ Picture Window**



**Standard Features:**

- Custom manufactured to your specifications or job requirements.
- EnergyMiser™ Triple Pane, Soft Coat Low-E glass yields a R6 Insulation value and a .16 U-Factor
- Fusion welded, multi-chambered 3 ¼” vinyl master frames.
- DuraSeal Warm Edge Spacer.
- Low Profile frame for maximum visibility.

**Options:**

- AccuBond™ Custom Color Match for Exterior
- Decorative Colonial or Georgian grids
- Tempered or Obscured glass

**FULL WINDOW PERFORMANCE RATINGS**

<b>U-Factor (Insulation Value)</b>	Double Glass = .26 (R4)	Triple Glass = .16 (R6)
<b>Condensation Resistance</b>	Double Glass = 62	Triple Glass = 74
<b>Visible Transmittance</b>	Double Glass = .61	Triple Glass = .48
<b>Solar Heat Gain Coefficient</b>	Double Glass = .31	Triple Glass = .27

ANSI/NFRC 100-2020: Procedure for Determining Fenestration Product U-Factors  
 ANSI/NFRC 200-2020: Procedure for Determining Fenestration Product Solar Heat Gain Coefficient and Visible Transmittance at Normal Incidence  
 NFRC 500-2017: Procedure for Determining Fenestration Product Condensation Resistance Values  
 Program Versions Utilized: THERM/WINDOW 7.4;NFRC 101-2020[E1A9];NFRC Sim Manual 2020